PTM Drum / Wheelchair Platforms



The PTM low profile platform is a versatile scale that is ideal for weighing drums, barrels and wheelchairs.. The easy access ramps on both sides offers smooth transitions from the floor to the weighing platform and the diamond checked platform offers a durable weighing area. With handles and wheels for easy portability the PTM can be used where it's needed in a warehouse or medical environment.

The PTM is available with the GK indicator or AE 402 indicator to give a range of different features and functions. The long cable lets the indicator be placed where it needs out of the way of the platform. The GK indicator allows for a numeric tare value to be entered where the AE 402 is IP67 sealed for dust and moist environments.

With over four decades of experience in the production of weighing equipment you can trust Adam for quality products that offer a range of features designed for many different applications



















PTM Series

PTM platform scale feature a low profile design for easy loading and unloading. The range incorporates a non-slip checkered plate for added grip.

Heavy duty rubber feet support the four loadcells ensuring quality and longevity of the bases.

Features

- Adjustable levelling feet
- 4 loadcell construction
- 3 metres of loadcell cable
- Heavy duty rubber feet

GK Indicator

With a number of weighing modes and units the GK indicators can be adapted to a wider range of applications. A large backlit display is easy to read with a capacity tracker to help protect from overloading and the colored LED indicators are ideal for check weighing applications to measure underweight, overweight and acceptable limits. With standard RS-232 interface for computers and printers, rechargeable battery and AC adapter powered, and full numerical keypad, the GK offers the most value for an indicator.

Features

- Full tare range
- Accessible internal rechargeable battery
- Large backlit LCD display with capacity tracker
- Battery operation with auto-off to save battery life
- Check weighing LED lights to show acceptable limits
- Bi-directional RS-232 output for connection to computers and printers

AE 402 Indicator

The AE 402 is a multi-purpose weighing indicator that can be used for a wide range of applications. With a large easy-to-read backlit LCD display this indicator provides faster readings. The AE 402 offers digital filters, memory accumulation, tare, display hold, RS-232 interface, plus an internal rechargeable battery and an AC adapter included.

Features

- Hold Function
- · Full range tare
- Backlit LCD display
- Wall mount bracket
- Supports upto four 350 ohm loadcells
- Bi-directional RS-232 interface

Technical Specifications

PTM Series

Model	Maximum Scale Capacity (lb/kg)	Platform Size (in/mm)	Height (in/mm)	Net Weight (lb/kg)	Cable	Construction	
PTM	1100lb / 500kg	760mm x 580mm	70mm	33.5kg	3m long	Mild Steel	

GK Indicators

Model	Sensitivity	Loadcells	Zero input range	Signal Range	Weighing Units	Readability
GK	Up to 1:30,000	Up to 4 x 350ohm loadcells	0 - 10mV	0 - 40mV	g, kg, lb, oz, lb:oz	Selectable

AE 402 Indicators

Model	Sensitivity	Loadcells	Zero input range	Signal Range	Weighing Units	Readability
AE 402	0.15uv/d	Up to 4 , 350 ohm loadcells – Minimum 87ohms, maximum 1120ohms	0- 10mv	0+40mv	lb / kg	Selectable

Accessories

- Item No. 8023 Adam Printer
- Item No. 9665 In-Use Cover for GK
- Item No. 9192 Thermal replacement paper (5-pack)

