

CBS10/15/20-J


1.0-2.0Ton Semi-electric Fork Over Stacker

Lifting Height: 1600-3500mm



Advantages

- ❏ Brake on the universal wheel. It is light and fast to stop the stacker by foot brake.
- ❏ The whole set is with fine workmanship, smooth lines, elegant appearance. Double coating on the entire stacker makes it scratch resistance, anti-rust, and durable.
- ❏ External battery charger is better in heat dissipation. Unlike the built-in charger, it avoids the damages caused by vibration.
- ❏ Adjustable bolts in rear part of the fork. When the stacker is used for many years or the forks are not level caused by other factors, the users can adjust the bolts to make the forks level.
- ❏ With special process manufactured Nylon wheel is wear and pressure resisting, quiet, light, flexible and with small resistance.
- ❏ Using the best hydraulic cylinders and oil system, together with the fine process, minimize the leak possibility.



Feature													
Model		CBS1016	CBS1020	CBS1025	CBS1030	CBS1035	CBS1516	CBS1520	CBS1525	CBS1530	CBS1535	CBS2016	CBS2020
Max. capacity	kg	1000				1500				2000			
Capacity at max.lifting height	kg	1000	800	700	600	500	1500	1200	1050	900	750	2000	1600
Dimension													
Max.Lifting height	mm	1600	2000	2500	3000	3500	1600	2000	2500	3000	3500	1600	2000
Load center	mm	450											
Forks length	mm	900/1100											
Forks width	mm	150											
Outside width of the forks	mm	550/640											
Min.height of the forks	mm	85											
Length of the support legs	mm	875											
Width of the support legs(single)	mm	100											
Outside width of the two support legs	mm	490/590				590	490/590				590	490/590	
Turning radius	mm	1350											
Min.Aisle width for pallet 800×1200	mm	2250											
Min.Aisle width for pallet 1000×1200	mm	2040											
Overall length	mm	1600(900)/1800(1100)											
Overall width	mm	760											
Max.extend height	mm	2077	2567	3067	3567	4067	2077	2567	3067	3567	4067	2077	2567
Mast lowered height	mm	2077	1577	1827	2077	2327	2077	1577	1827	2077	2327	2077	1577
Electrical configuration													
Battery	V/AH	12/120,(10-12V)											
Charger	V/A	12/20											
Power unit		DC,12V,1.5KW											
Weight													
Service weight	kg	315	365	374	380	405	320	374	385	395	415	325	380

*Details of specifications and equipment are based on information available at time of printing and may change without notice.

ANHUI HELI INDUSTRIAL VEHICLE IMP.AND EXP.CO.,LTD.