



## SL-CLASSIC-UB ◀ 140 cm ▶



### Cabinet for acids and alkalis

#### SL-CLASSIC-UB model SL.060.140.UB.3T

in Light grey (RAL 7035), interior equipment with 4 x pull-out shelf (panel/PP)

Order No. 30616-001-30618



### Cabinet for acids and alkalis

#### SL-CLASSIC-UB model SL.060.059.UB.T

in Light grey (RAL 7035), interior equipment with 2 x pull-out shelf (panel/PP)

Order No. 30622-001-30625

**Safe and approved storage of aggressive, non flammable hazardous materials in working areas**

### Function / construction:

- **robust construction and longevity:** made out of highly resistant melamin resin special plates
- **user-friendly:** access to all containers, 135° opening of the wing door, interior of the cabinet completely visible
- **no unauthorised use:** doors lockable with cylinder lock and locking state indicator (red/green)
- **mobile:** castors with plinth (optionally available), easy moving of the cabinet
- **ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system

### Available equipment

- pull-out shelves with removable plastic sump
- **model SL.060.140.UB:** right compartment with integral shelf for material storage



### Cabinet for acids and alkalis

#### SL-CLASSIC-UB model SL.060.110.UB.2T

in Light grey (RAL 7035), interior equipment with 4 x pull-out shelf (panel/PP)


Order No. 30619-001-30621

### Technical data


		SL.060.140.UB.3T	SL.060.110.UB.2T	SL.060.059.UB.T
External dimensions W x D x H	mm	1400 x 570 x 600	1100 x 570 x 600	590 x 570 x 600
Internal dimensions W x D x H	mm	left: 489 x 531 x 562 central: 489 x 531 x 562 right: 281 x 531 x 562	all compartments: 489 x 531 x 562	488 x 531 x 562
Weight without interior equip.	kg	80	60	40
Extraction air	DN	50	50	50
Air change <b>30 times</b>	m³/h	9	9	4
Diff. pressure (air change <b>30 times</b> )	Pa	10	10	5
Distributed load	kg/m²	82	93	151
Maximum load	kg	100	100	100




SL.060.140.UB.3T Front view




Side view




Top view




SL.060.110.UB.2T Front view




Side view




Top view




SL.060.059.UB.T Front view



Side view



Top view



SL-LINE

Model	Information / equipment	Order No.
SL.060.140.UB.3T	without interior equipment, Underbench cabinet, with 3 wing doors	30616
SL.060.110.UB.2T	without interior equipment, Underbench cabinet, with 2 wing doors	30619
SL.060.059.UB.T	without interior equipment, Underbench cabinet, left hinged, with wing door	30622
SL.060.059.UB.TR	without interior equipment, Underbench cabinet, right hinged, with wing door	30623

Body colour	Door colour	Order No.
Light grey RAL 7035	Light grey RAL 7035	001 <b>4</b>

Interior equipment packages (can only be ordered in combination with the cabinet)	Material	Order No.
Width 1400 mm		
left: 1x pull-out shelf (V=11.0L)	panel/PP	30617 <b>2</b>
right: 1x pull-out shelf (V=11.0L)		
left: 2x pull-out shelf (V=11.0L)	panel/PP	30618 <b>2</b>
right: 2x pull-out shelf (V=11.0L)		

Interior equipment packages (can only be ordered in combination with the cabinet)	Material	Order No.
Width 1100 mm		
left: 1x pull-out shelf (V=11.0L)	panel/PP	30620 <b>2</b>
right: 1x pull-out shelf (V=11.0L)		
left: 2x pull-out shelf (V=11.0L)	panel/PP	30621 <b>2</b>
right: 2x pull-out shelf (V=11.0L)		

Interior equipment packages (can only be ordered in combination with the cabinet)	Material	Order No.
Width 590 mm		
1x pull-out shelf (V=11.0L)	panel/PP	30624 <b>2</b>
2x pull-out shelf (V=11.0L)	panel/PP	30625 <b>2</b>

Interior equipment	Material	For cabinet width	1)	2)	3)	Order No.
pull-out shelf, with PP sump	panel/PP grey	590, 1100 and 1400	25.00	18.00	16.36	30770 <b>2</b>
castors with plinth, height = 30 mm	sheet steel powder-coated RAL 7035	1400				30374 <b>2</b>
castors with plinth, height = 30 mm	sheet steel powder-coated RAL 7035	1100				30362 <b>2</b>
castors with plinth, height = 30 mm	sheet steel powder-coated RAL 7035	590				30478 <b>2</b>

Accessories	Order No.
extraction module without exhaust air monitoring for wall mounting	17178 <b>2</b>

\* usable storage space W x D (mm)

1) load capacity (kg), 2) retention capacity (ltd), 3) maximum container volume in the cabinet (ltd)



**Safe and approved storage of aggressive, non flammable hazardous materials in working areas**

## Function / construction:

- **robust construction and longevity:** made out of highly resistant melamin resin special plates
- **user-friendly:** access to all containers, 135° opening of the wing door, interior of the cabinet completely visible
- **no unauthorised use:** door lockable with cylinder lock and locking state indicator (red/green)
- **mobile:** castors with plinth (optionally available), easy moving of the cabinet
- **ventilation:** integrated air ducts ready for connection (DN 50) to a technical exhaust system

## Available equipment

- pull-out shelves with removable plastic sump

### Cabinet for acids and alkalis

#### SL-CLASSIC-UB model SL.080.110.UB.2T

in Light grey (RAL 7035), interior equipment with 4 x pull-out shelf (panel/PP)

Order No. 33200-001-30621



#### castors with plinth

**stable** – easy moving of the cabinet

**safe fixing of the cabinet** – integrated locking mechanism

**flexible** – height adjustment to various laboratory furniture



### Cabinet for acids and alkalis

#### SL-CLASSIC-UB model SL.080.059.UB.TR

in Light grey (RAL 7035), interior equipment with 2 x pull-out shelf (panel/PP)

Order No. 33202-001-30625

## Technical data

External dimensions W x D x H  
Internal dimensions W x D x H  
Weight without interior equip.  
Extraction air  
Air change **30 times**  
Diff. pressure (air change **30 times**)  
Distributed load  
Maximum load

### SL.080.059.UB.TR


mm 590 x 570 x 800  
mm 490 x 530 x 760  
kg 48  
DN 50  
m³/h 6  
Pa 5  
kg/m² 157  
kg 100

### SL.080.110.UB.2T


1100 x 570 x 800  
all compartments: 1000 x 530 x 760  
73  
50  
9  
10  
98  
100




SL.080.110.UB.2T Front view




Side view




Top view




SL.080.059.UB.TR Front view



Side view



Top view



SL-LINE

## Order example - how to order correctly



30623



001



30625



## Model

SL.080.110.UB.2T  
SL.080.059.UB.TR

## Information / equipment

without interior equipment, Underbench cabinet, with 2 wing doors  
without interior equipment, Underbench cabinet, right hinged, with wing door

## Order No.

33200  
33202

## Body colour

Light grey RAL 7035

## Door colour

Light grey RAL 7035

## Order No.

001 4



## Interior equipment packages (can only be ordered in combination with the cabinet)

## Width 1100 mm

left: 1x pull-out shelf (V=11.0L)  
right: 1x pull-out shelf (V=11.0L)  
left: 2x pull-out shelf (V=11.0L)  
right: 2x pull-out shelf (V=11.0L)

## Material

panel/PP  
panel/PP

## Order No.

30620 2  
30621 2

## Interior equipment packages (can only be ordered in combination with the cabinet)

## Width 590 mm

1x pull-out shelf (V=11.0L)  
2x pull-out shelf (V=11.0L)

## Material

panel/PP  
panel/PP

## Order No.

30624 2  
30625 2

## Interior equipment

pull-out shelf, with PP sump  
castors with plinth, height = 30 mm  
castors with plinth, height = 30 mm

## Material

panel/PP grey  
sheet steel powder-coated RAL 7035  
sheet steel powder-coated RAL 7035

## W x D x H (mm)

590, 1100 and 1400  
1100  
590

1)



2)



3)

## Order No.

25.00  
18.00  
16.36  
30770 2  
30362 2  
30478 2

## Accessories

extraction module without exhaust air monitoring for wall mounting

## Order No.

17178 2

\* usable storage space W x D (mm)

1) load capacity (kg), 2) retention capacity (ltd), 3) maximum container volume in the cabinet (ltd)